

05/15/98
65705 U.S. PTO

65705 U.S. PTO
09/735299
05/15/98

Express Mail No: EM 000783532US
Attorney Docket: WRIPLASTIC-Div

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: 08/525,639 New Serial No.: _____

Filed: September 6, 1995 New Filing Date: _____

Group Art Unit: 1106 New Group Art Unit: _____

Examiner: Nina Bhat New Examiner: _____

LETTER OF TRANSMITTAL

The Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Dear Commissioner:

Enclosed for filing are the following documents:

- a. a Preliminary Amendment to be entered with this filing prior to calculation of the filing fee;
- b. copies of parent application serial number 08/525,639, including copies of the original specification, original claims and informal drawing, the original combined declaration and power of attorney, the verified statement establishing small entity status (independent inventor), the verified statement establishing small entity status (non-profit organization), and the assignment of patent rights;
- c. a new formal drawing (1) sheet;
- d. Information Disclosure Citation with copies of the cited references;

- e. Information Disclosure Statement under 37 CFR 1.97 & 1.98;
- f. This Letter of Transmittal, a fee calculation sheet and a cashier's check in the amount of \$395.00; and
- g. Express Mail Certificates for each document.


Please confirm receipt of the documents by applying your date stamp and serial number on the enclosed postcard and returning it to me.

Dated: May 15, 1998

Respectfully Submitted,

SANTANGELO LAW OFFICES, P.C.

By:



Brit Nelson
ATTORNEY FOR APPLICANT
PTO No. 40,370
125 South Howes, Third Floor
Fort Collins, Colorado 80521
(970) 224-3100

wri\plastic\us\div\div.xmt

FEE CALCULATION SHEET
USPTO Patent Application

(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
TOTAL CLAIMS ¹	16-20 =	0	x \$22.00 =	\$0.00
INDEP. CLAIMS	2-3 =	0	x \$82.00=	0.00
MULTIPLE DEPENDENT CLAIMS (insert Y or N)				
BASIC FEE				790.00
TOTAL OF ABOVE =				790.00
REDUCTION BY 50 % FOR FILING BY SM ENTITY (insert Y or N)			Y	395.00
ASSIGNMENT (insert Y or N)			N	\$ 0.00
TOTAL =				\$ 395.00

¹ TOTAL CLAIMS BASED ON:

16	Numbered claims with:
2	Independent claims (Claims 1, 2)
14	Claims dependent on a single claim (Claims 3-16)
	Claims dependent on a two claims
	Claims dependent on a three claims
	Claims dependent on a four claims
	Claims dependent on a five claims
16	TOTAL CALCULATED CLAIMS

Note: Fees based on October 1, 1997

Express Mail No: EM 000783532US
Attorney Docket: WRIPLASTIC-Div

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: 08/525,639 New Serial No.: _____

Filed: September 6, 1995 New Filing Date: _____

Group Art Unit: 1106 New Group Art Unit: _____

Examiner: Nina Bhat New Examiner: _____

CERTIFICATE OF EXPRESS MAILING

I, Barbara Graves, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Letter of Transmittal, Fee Calculation Sheet and cashier's check in the amount of \$395.00 with the United States Postal Service as "Express Mail" for mailing to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

DATED: May 15, 1998

Barbara Graves
Barbara Graves

08/525,639

Express Mail No: EM 000783532US
Attorney Docket: WRIPLASTIC-Div

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: 08/525,639 New Serial No.: _____
Filed: September 6, 1995 New Filing Date: _____
Group Art Unit: 1106 New Group Art Unit: _____
Examiner: Nina Bhat New Examiner: _____

PRELIMINARY AMENDMENT

Before calculating the fees on the above examination and before examining the above-referenced application, please amend the application as follows:

In the claims:

Please cancel claims 17 - 22.

REMARKS

The claims have been amended to cancel claims 17 - 22 in the original application, leaving claims 1 - 16. In the parent application, the Examiner required a restriction of claims 1 - 16. Therefore, this preliminary amendment narrows the pending claims to those claims required by the restriction.

The enclosed fee sheet is based on the claims remaining after this preliminary amendment.

The Formal Drawings


The Applicants file the formal drawing submitted in the parent application as amended in the prosecution of that application.

CONCLUSION

The Applicants submit the method claims from the parent application that were restricted and requests that the Examiner allow the claims at an early opportunity.

Dated this 15 day of May, 1998.

Respectfully submitted,
SANTANGELO Law Offices, P.C.



Brit Nelson
ATTORNEY FOR APPLICANT
PTO No. 40,370
125 South Howes, Third Floor
Fort Collins, Colorado 80521
(970) 224-3100

wri\plastic\us\div\prel.amd

Express Mail No: EM 000783532US
Attorney Docket: WRIPLASTIC-Div

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling


Serial Number: 08/525,639 New Serial No.: _____
Filed: September 6, 1995 New Filing Date: _____
Group Art Unit: 1106 New Group Art Unit: _____
Examiner: Nina Bhat New Examiner: _____

CERTIFICATE OF EXPRESS MAILING

I, Barbara Graves, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.
2. I have this day deposited the attached Preliminary Amendment with the United States Postal Service as "Express Mail" for mailing to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

DATED: May 15, 1998



Barbara Graves

I. TECHNICAL FIELD

5 The present invention relates generally to processes for low
temperature thermal decomposition of waste plastics. Specifically, the
invention focuses upon achieving decomposition of waste plastics at a lower
temperature than was previously possible. In particular municipal, health and
industrial waste plastics are processed such as (but not limited to) polyethylene
10 (PE), polypropylene (PP), polystyrene (PS), polyethylene terephthalate (PET),
polyurethane (PU), and polyvinyl chloride (PVC).

II. BACKGROUND ART

15 Waste plastics, that is synthetic polymer-containing substances, pose an
environmental issue because of the problems associated with disposal: a large
volume of non-biodegradable material. Because of the limits on landfill
capacity, future recycling or decomposition is a necessity. Direct recycling
back to the manufacture is not always feasible because such waste plastic is
often mixed with respect to polymer type and separation is uneconomical.
20 Economical considerations for processing waste plastic often require the use of
the unseparated mixed waste plastic. Plastic recycling originated with the
manufacture of synthetic thermoplastics. Rejected parts, trim, and flash from
operations represented valuable materials that were ground and recycled with
virgin material. This process was potentially repeated a number of times
25 provided the percentage of regrinds remained low. As long as the plastic scrap
generated by the industry was clean and uncontaminated with other plastics,
reprocessing within the industry continued to expand, provided the price of
virgin plastic remained high. After 1960 with a decrease in prices, profit
margins for plastic scrap were squeezed, and disposal instead of reprocessing
30 often occurred.

35 After 1970, plastic prices rose again due to OPEC raising the
cost of petroleum feedstocks and recycling practices again increased. Interest
increased not only in processes for reclaiming waste plastics, such as product
evaluation for chemicals and fuels, but also in the necessary step of separation

of plastics from other waste material. A review of this early history of plastics recycling is given by R.J. Ehrig in *Plastics Recycling*, Oxford University Press, NY, 1992, hereinafter referred to as Ehrig (1992). Some of the early operating plants for recycled plastic included a Department of Energy funded plant in LaPorte, Texas, which used a fluidized bed of sand and was designed for 17 million pounds per year of atactic polypropylene. It ran from 1980-82. In 1984 at Ebenhausen, Germany, a 20 million pound per year plant used molten salt with a fluidized bed reactor to process plastic wastes and tires.

In all cases economics governed whether such plants continued operation. Since 1985 plastics recycling has become more economically feasible due to continued plastics technological growth and increased environmental concern, however, significant cost impacts remain due to the level of the elevated temperatures previously required.

III. DISCLOSURE OF INVENTION

The present invention relates to a process which overcomes the above-mentioned deficiencies in the prior art and to a process which achieves decomposition of waste plastic at a relatively low temperature. As one example, the process decomposes a mixed stream of waste plastic at a temperature generally less than 375°C in a hot oil medium. The process converts the polymeric structure of the waste plastic or plastics to smaller chemical molecules such as the monomeric units and related chemical structures at a relatively lower temperature. It also serves the market for the such products. Since this market is not a to-be-developed manufacturing process, but rather one for which existing plants in the refining and petrochemical industries already exist, the process is adaptable to existing facilities that are already experiencing limited supplies of low molecular-weight, heteroatomic free feedstocks from petroleum crude oils. The low-molecular weight distillate from waste plastic processing according to this invention may help reduce the demand for imported petroleum products and help decrease our dependence on foreign crude oil.

Basically the process is one in which the materials to be reacted are added or controlled so as to assure the existence of sufficient or appropriate amounts of free radicals. These free radicals are included to initiate free radical chain depolymerization reactions known to "unzip" polymer structures. To avoid recombination and to further enhance the process, this reaction is accomplished in a diluent such as an oil.

IV. BRIEF DESCRIPTION OF THE DRAWING

Figure 1 shows a schematic diagram of a system for processing recycled waste plastic according to one technique of the present invention.

V. BEST MODE FOR CARRYING OUT THE INVENTION

The subject invention processes or decomposes mixed waste plastic at a relatively very low temperature. It may use thermal degradation in an oil media. Typical thermal degradation of waste plastics, such as that associated with municipalities waste, has previously required 400-600°C. Through the present invention, this may occur at below about 375 °C. This represents a saving of energy requirements and capital costs. In basic form, the invention is a process for the low-temperature thermal decomposition of waste plastics by a free radical mechanism at temperatures below 375°C. This may be accomplished in a diluent such as oil. This diluent does not significantly impact the action of the free radicals, serves to maintain energy levels, reduce chemical interaction, and serves as a diluent so as to avoid recombination of reactive products. As those skilled in the art could readily ascertain, the free radicals are neutral, unpaired electron shell substances which initiate the process and may be provided by a free radical precursor. These precursor substances are essentially all substances capable of providing free radicals at the condition chosen for the reactant. As those skilled in the art would also readily understand, they may include certain plastic resins (ie. polyvinyl chloride, polyurethane, and most likely nylon 66) and almost any other materials which produce the free radicals, such as those materials containing carbon-carbon, carbon-nitrogen, carbon-oxygen, or carbon-sulphur bonds as well some other compounds which may be free radical initiators and which do

not volatilize too rapidly in the reacting conditions chosen. The free radical precursors may exist as part of the waste plastic, may be a separately added substance, or may even be added to the diluent. The low-temperature activity of the present invention is believed to be attributed to the free radical chain depolymerization reactions known to "unzip" synthetic polymer structures. The free radical(s) liberated from polyvinyl chloride or from other sources at temperatures below 375°C act as initiators to start the process. In an oil, free radicals from the initiator attack the polymer structure to satisfy their electronic structures. This results in the abstraction of a proton from the polymer molecule which initiates the free radical process in the polymer chain to break the structure into smaller molecules. The result is decomposition of the plastic at temperatures lower than previously expected. The resultant products are likely to be a distillate, coke, noncondensable hydrogen, and other gases.

In establishing the preferred embodiment of the invention, it is believed that there are three important conditions for low-temperature thermal decomposition of such plastics to occur. First, the plastic may need to be diluted in a diluent such as an oil solution to prevent recombination reactions. Second, if the free radical initiators are generated from the waste plastic, the plastics composition must contain resin types, such as polyvinyl chloride, that decompose at temperatures below 375°C to generate free radicals. Third, even though the initiator concentration must be low, in a continuous process, it appears necessary to maintain the level at a critical concentration of about 0.5% (wt) to maintain the reaction.

As mentioned, the oil is believed to serve a variety of functions. In addition to those previously mentioned, it may act as a diluent which limits termination reactions that produce the higher molecular weight species as discussed above. It may also serve as a heat transfer media to ensure uniform heating of the waste plastics. The nature of the oil utilized in the process does not appear to be critical to many waste plastic degradation applications, but it may change the technical processing requirements. One choice is used motor

oil since it, itself is waste material. Yet other oils include but are not limited to heavy oils (that is, oils not distillable at the conditions chosen for the reactant or about 1 atmosphere pressure at up to 400 °C), fluidized bed catalytic cracker slurry oil, distillation tower vacuum bottoms, and heavy heating or bunker oil.

The stability of the oil at process conditions may impact the ability to recycle the oil as well as the amount of overhead distillate formed. Low value oils, that is oils either high in elements other than carbon and hydrogen oils of high molecular weight, particularly aromatic substances, or substances having a low hydrogen to carbon atomic ratio may also be used. This can afford a significant economic advantage as such substances are likely to be undesirable for other purposes and may be readily available at refinery sites. In addition, utilization of low value oils in the process of the present invention can create a result which basically can be characterized as combining two undesirable or waste materials to create a desirable and useful material.

As mentioned a distillate may be formed. This may include a general hydrocarbon material whose volatility allows it to become overhead vapor material under certain conditions. For the preferred embodiment, this occurs at approximately 375 °C under nominal pressure of about one atmosphere. Importantly, the products of the process may be materials which either have economic value and can be utilized in the market place, can be consumed by the process, or can be safely released to the environment.

For most situations the common range of normal volatility for distillate formed from mixed waste plastics according to this process is about 40-375 °C. Higher boiling hydrocarbon materials remain with the heavy oil. The distillate products may contain components that could be classified as value-added products (ie. toluene and styrene). These are not usually produced by the present process as pure compounds in the distillate. Instead they are likely to be present in complex mixtures with other hydrocarbon species in the preferred embodiment. Naturally, separation may be achieved

to obtain these components in pure form. This may occur on site if the economics warrant. Alternatively, the distillate or products may be marketed without additional separation. The whole distillate may have market value as a feedstock to the petrochemical and refining industries. The use of these distillates or products in the refining industry is attractive because the types of compounds present indicate they might be useful as octane additives for the production of unleaded gasoline. The aromatic compounds (toluene, ethylbenzene, etc.), and the branched and cyclic structures are known to have relatively high octane numbers which can be used to enhance the octane rating of gasoline.

Five waste plastics may be considered as often included in a typical waste plastic stream. These are polyethylene (PE), polypropylene (PP), polystyrene (PS), polyethylene terephthalate (PET), and polyvinyl chloride (PVC). Thayer reported a distribution for municipal wastes of PE: 63%, PS: 11%, PP: 10%, PET: 7%, PVC: 5%, Other: 4%; See Solid Waste Concerns Spur Plastic Recycling Efforts, Chemical & Engineering News, p7, January 30, 1989; hereinafter Thayer (1989). By ignoring the remaining 4%, this information produced the basis for one common mixed waste plastic experimental composition.

Figure 1 shows a typical process system in schematic form. The raw mixed waste plastic is supplied by a first supply means 10 and is fed to a mechanical chopper 11 which produces a chopped up, or comminuted, plastic material 12. This chopped mixed waste plastic 12 enters a lock hopper 20 or some mix means which may mix it with a diluent supplied by a second supply means 25. It may also store the mix and meter it 21 into a solution tank 22 that is well stirred or mixed 23 (potentially continuously) and has an appropriate amount of diluent such as oil from second supply means 25 or from recycling mixed with it at about 200 °C. The lock hopper 20 may include some type of star valve to prevent the escape of vapor. Further, the solution tank 20 may be utilized to assure that the plastic is solubilized in the heavy oil that is recycled to this tank from farther through the process. The oil flux through this tank may thus be maintained to allow sufficient residence

time in the tank to ~~lub~~ubilize the plastic.

5 The oil may be cycled through from further down the process and may additionally contain a selected amount of new oil 47. The ratio of oil to plastic may not be critical but a range of from about 2:1 to 10:1 oil to plastic appears to work. This solution of oil and plastic 24, may be stirred 23 at all times. The system may have an injected free radical precursor 32 which may enter the reaction container 41 at some control means 40. This may include some type of controllable valve and may also include some type of controlling logic 33. This may act to control the content of the solution to assure that it will contain a sufficient free radical content when heated so that substantially all waste plastic is decomposed. The free radical precursor 32 may be injected when needed by monitoring and sensing the conditions within the reaction container 41. If the overhead 43 decreases sufficiently (most likely sensed by an increase in the reactant temperature ascertained or a decrease in the amount of heat needed to maintain a given reactant temperature), it likely indicates that the relative amount of free radical precursor has dropped so more free radical precursor 32 may be automatically added. (Naturally, only the relative proportions are involved so one could conversely hold the amount of free radical precursor 32 steady and adjust the amount of waste plastic.)

15 Preferably the free radical precursor 32 is chosen to decompose at or below the nominal reactor temperature into some free radical or free radicals. Thus, acceptable free radical precursors include polyvinyl chloride, polyurethane, and other materials that will thermally form free radicals at temperatures at or below the reaction temperature selected. These free radical precursors may be stored in some third supply means 31 until use and may even be waste plastic themselves.

25 30 The reaction container 41 may be well stirred 42 and may have entering the solution of oil, plastic, and precursor material, cycled back heavy oil 44, and some new heated oil 45. Again, the residence time in the reactor or reaction container may be maintained to maximize plastics conversion.

Further, product gas may be recycled through the head space of the reactor to aid in removing volatiles from the reaction zone.

As shown, the reactor heavy oil 46 leaves and passes through a multipurpose heat exchanger or temperature control means 48 (such as a heater) where it is heated or cooled depending upon conditions of operation and leaves 49 to be pumped 50, cycled back 44, exited 51, or fed to the solution tank 22. This residual heavy oil may suffer some thermal degradation and may contain a portion of the plastic degradation that is not thermally decomposed. Thus, some heavy oil may be discharged 51 and fresh oil 47 inserted. In many instances the amount of oil or heavy oil recycled 44 may be in the range of approximately 70-90 percent, preferably about 80-85 percent, of the reactor fluid. Yet the process will usually work with a heavy oil recycle amount from zero to about 95 percent. Zero, or no, heavy oil recycled means a straight through flow process.

The multipurpose heat exchanger 48 may act as a regenerative heater for the fresh oil 47, which may be preheated by the recycled heavy oil entering 46 and leaving 49, before entering 45 the reaction container 41. It also may serve to heat the reactor heavy oil as heavy oil recycle 44 to keep the reaction temperature adequate. This normally has a range of about 300-375 °C. This heating operation can involve a heat source such as steam, burned fuel, fuel from the overhead gas 60, or coke and other solids formed from plastic decomposition and subsequently recovered material.

The reactor overhead 43 potentially consists of three components: a noncondensable overhead gas 60, a condensable liquid stream of overhead distillate 64 that is collected and stored 65, and condensable overhead specialty decomposition substances 66. Thus the condenser 61 or some collection means can be two-staged. The first stage may condense, perhaps in a modified cyclone arrangement, any such overhead specialty decomposition substances. These are usually solid 66, and largely come from PET degradation. The second stage may operate with cooled water 62 which then

leaves 63 and condenses the overhead distillate 64, the remainder process product. Thus the amount of PET in the mixed waste plastic may govern how much solid is potentially present and collected. Also a small amount may be handled by becoming entrapped in the heavy oil 51. The overhead gas 60 may pass through the condenser 61 unaffected; however, before further use it can be water scrubbed to remove HCl or other halide acids.

Various equivalent flow sheets are possible and that shown in Figure 1 is only one of many potential that could carry out the subject invention.

EXPERIMENT 1

Before mixed plastic wastes were studied, each individual component plastic was thermally decomposed to have a basis for the difference between mixed and individual resource recovery, and whether the mixed plastic wastes when thermally decomposed had an unexpected interaction.

The thermal decomposition was performed in hot fresh oil, usually at temperatures between 375 and 450°C, as a convenient substance that dissolved the plastics. Further, used or waste motor oil was a convenient fresh oil source and in itself represented a waste product. Other fresh oils that were mostly stable below 450 °C were employed such as fluidized bed catalytic cracker Slurry oil, distillation tower vacuum bottoms, and heavy heating or bunker oil. For convenience, most studies employed a simulated used or waste motor oil which was SAE 50 motor oil.

A laboratory setup was used for preliminary experimentation which consisted of a thermally regulated flask with water condenser. The flask temperature was regulated to within 5 °C and the overhead distillate condensed with 16 °C water while the amount of uncondensed overhead gas was measured. The SAE 50 oil and the appropriate plastic resin were placed into the flask and the flask was purged with nitrogen before heating began. After the proper time at temperature, the flask was quenched.

The range temperatures was 375 to 450 °C for most plastics; however, PVC and PET were too reactive at these temperatures and their range was reduced to 285 to 360 °C. The reaction time varied up to one hour in 15 minute increments.

The important individual results which varied with the type of plastic were as follows:

PE: With 75% oil and 25% PE starting and a 45 minute operating time, little overhead distillate was condensed below 425 °C but here 9.0% of the total product mix was overhead distillate. At 450 °C 28.6% was distillate indicating some of the original oil had been decomposed. Heavy oil containing some decomposition products remained in the flask. For all temperatures no measurable coke was produced and the overhead gas was less than 2.5%. For the time varying experimentation at 425 °C, the overhead distillate increased with time peaking at 11.3% at one hour. A gas chromatography/mass spectrometry detailed study of the 425 °C overhead distillate indicated over 64 organic compounds and the 15% majority was classified as a mixture of C₄ substituted cyclopentanes:

PP: With 75% oil and 25% PP starting and a 45 minute operating time, little overhead distillate was condensed below 400 °C but here 9.5% of the total product mix was distillate. At 425 °C 14.9% was distillate with apparently minuscule oil decomposed. Heavy oil containing some decomposition products remained in the flask. For all temperatures investigated no measurable coke was produced, and the overhead gas was less than 2.0%. For the time varying experimentation at 425 °C, the overhead distillate increased with time peaking at 18.6% at one hour. A gas chromatography/mass spectrometry detailed study of the 425 °C overhead distillate indicated over 55 identified organic compounds and the 5.9% majority was identified as 1,4 pentadiene with a close second at 5.3% classified as C₄ substituted octane.

PS: With 75% oil and 25% PS starting and a 45 minute operating time, little overhead distillate was condensed below 390 °C but here 7.0% of the total product mix was overhead distillate. At 425 °C 33.7% was overhead

distillate indicating some of the oil had been decomposed. Heavy oil containing some decomposition products remained in the flask. For all temperatures no measurable coke was produced and the overhead gas was less than 1.5%. For the time varying experimentation at 400 °C, the overhead distillate increased with time peaking at 18.9% at one hour. A gas chromatography/mass spectrometry detailed study of the 400 °C overhead distillate indicated over 49 identified organic compounds and the large 33.2% majority was identified as styrene.

PVC: With 89% oil and 11% PVC starting and a 45 minute operating time, little overhead distillate was condensed even at 360 °C, the maximum temperature employed, but here only 1.2% of the total product mix was overhead distillate. Heavy oil containing some decomposition products remained in the flask. For all temperatures coke production increased with temperature and was 7.8% at maximum temperature. Except for HCl, overhead gas production was always minimal. HCl production was constant at 6.1% with no temperature variation and apparently most chlorine appeared in this form.

PET: With 86% oil and 14% PET starting and a 45 minute operating time, no overhead distillate was condensed. At 375 °C, the maximum temperature employed, a Solid product of 7% of the total product mix was obtained, and this was likely terephthalic acid and/or benzoic acid. This solid product sublimed and collected largely in the flask neck making the material balance less accurate. Heavy oil containing some decomposition products remained in the flask. For all temperatures coke production decreased with temperature and was 15% at 325 °C but only 6% at 375 °C. Overhead gas production was always minimal.

EXPERIMENT 2

A review of the tests in Experiment 1 indicated that the apparent optimum temperature for hot oil decomposition of PE and PP was about 425 °C, about 400 °C for PS, about 375 °C for PET, and about 325 °C for PVC. Thus a temperature staging process was employed with mixed waste plastic, often called mixed resins. However PET was not employed in this experiment

since its solid decomposition product tended to clog the apparatus. A further aspect in omitting PET was that recent trends in recycling of waste plastic have been to separate out the bottles made of PET and recycle them directly to the bottle manufacturer.

A three stage temperature experiment was performed using 270 °C for 20 minutes, 410 °C for 30 minutes, and 450 °C for 45 minutes. The oil to mixed resins ratio was ten to one. The selected reactant mixed resins were proportioned to the amounts reported by Thayer (1989). Three different combinations of oil and sweep gas were employed, SAE 50 oil with and without nitrogen sweep gas, and fluidized bed catalytic cracker slurry oil with nitrogen sweep gas. The results are presented in Table 1 where the products section for distillate was the incremental distillate produced at that temperature. The total distillate was the sum of all distillate produced during the experiment. By summing over each experiment temperature, the cumulative distillate production was obtained. The heavy oil product represented the remaining input oil plus what product compounds remained dissolved in it.

Referring to Table 1, at all temperatures much of the SAE 50 oil was decomposed, and this large amount was unexpected from the results found from the individual components in Experiment 1. Evidently a free radical which promoted decomposition was occurring for even at the lowest temperature, 270 °C, the results of Experiment 1 indicated only PVC would decompose. Thus, the free radicals produced from PVC appeared to initiate the decomposition reaction of PE, PP, and PS, and as well as for the SAE 50 oil.

For the slurry oil experiment the free radical only affected the mixed resins as the slurry oil apparently did not decompose even at 450 °C. Further the mixed resins essentially decomposed completely at the lowest temperature of 270 °C. A further favorable aspect was that no measurable coke was formed with this slurry oil.

Table 1.
Material Balances for the Experiments Investigating
Temperature-Staged Thermal Decomposition of Mixed Plastics

Sweep Gas	None	Nitrogen	Nitrogen
Oil	SAE 50	SAE 50	Slurry Oil
Stage I, °C	270	270	270
Stage II, °C	410	410	410
Stage III, °C	450	450	450
Reactants			
Oil, g	100.00	100.00	87.45
PVC, g	0.60	0.60	0.44
Polystyrene, g	1.20	1.20	0.97
Polypropylene, g	1.10	1.10	0.88
Polyethylene, g	7.10	7.10	5.55
Total, g	110.00	110.00	95.29
Products			
Heavy Oil, g	27.08	18.82	89.25
Total Distillate, g	74.90	81.04	5.62
at 270°C	17.06	12.44	5.61
at 410°C	14.95	33.77	0.01
at 450°C	42.89	34.83	0.00
Hydrochloric acid, g	0.32	0.32	0.23
Coke, g	2.88	2.12	0.00
Gas, g	3.44	7.70 ^a	0.11 ^a
Total, g	108.62	110.00	95.21
Closure, %	98.7	100.00	99.9

^a Gas production determined by difference

EXPERIMENT 3

It appears from the previous experiments that sufficient free radicals were needed to enhance the rate of decomposition at the low temperatures. Thus, if the fraction of PVC was insufficient in the mixed waste plastic to generate enough free radicals, some source of additional free radical was added. The control mechanism for the process was based upon this action. Since the decomposition reactions were highly endothermic, if insufficient free radicals were present when adequate mixed resins were dissolved, the temperature of the system rose beyond the normal targeted 375 °C, and further the amount of distillate formed decreased significantly. To compensate, an additional source of free radicals was added to bring down the temperature and increase the distillate production. Extra free radical precursor up to about 10% of the waste plastic mix did not adversely affect the process.

This suggested that operating under about 375 °C was feasible to decompose the mixed resin and that the time factor was not critical. The fresh oil source is believed not crucial in many applications and apparently any available high-boiling oil that was processable by refinery operations was potentially usable.

The process can employ a wide range of input waste plastics ranging from pure PE, PP, PS, PET, and PVC, along with adequate free radical precursor added. Likewise any convenient mixture of such mixed plastics was usable as input to the process. Thayer (1989) reported that four percent of municipal waste plastic fell into an other category and was not separately identified. Yet this other category appeared processable by the subject invention since even if it did not decompose, it remained in the residual heavy oil. Further if it formed solids, recovery was with the coke and likely burned. Thus a separate group of mixed waste plastic is defined as 'other waste plastic' and consists of all other plastic types besides PE, PP, PS, PET, and PVC.

The products from this process have potential depending upon economics. These are in general overhead gas, overhead distillate, overhead specialty decomposition substances, residual heavy oil, and halide acids. The overhead distillate may potentially feed refinery stocks. Overhead gas may be burned for energy to heat the oil, or if not needed, may be flared. The halide acids, preferably hydrogen chloride, may be recovered as largely hydrochloric acid. The overhead specialty decomposition substances may be largely decompositions from PET, such as terephthalic acid and benzoic acid and may have good commercial potential if purified. The residual heavy oil and any coke may be burned. Products that are cycled back and burned to provide heat for the process are referred to as burnable products.

The foregoing discussion and the claims which follow describe a preferred embodiment of the present invention. Particularly, with respect to the claims, it should be understood that changes may be made without departing from the essence of the invention. In this regard it is intended that such changes would fall within the scope of the present invention. It simply is not practical to describe and claim all possible revisions to the present invention which may be accomplished. For instance, the claims are directed to both methods and apparatus. Although each have been included in various detail, they represent only initial claims directed toward only some basic aspects of the invention. The various permutations and combinations of the claims presented and of other aspects disclosed in the specification are intended to be encompassed within the claims and should be understood to be supported by the existing disclosure. Naturally, the disclosure of processes or methods should be construed to address apparatus utilized to achieve such processes or methods and should be construed to support a full scope of method and apparatus claims. While these may be added to explicitly include such details, the existing claims should be construed to encompass such aspects. In addition, the present disclosure should be construed to encompass subclaims similar to those presented in a process, method and apparatus context.

In addition, the extent any revisions utilize the essence of the invention, each would naturally fall within the breadth of protection encompassed by this patent. This is particularly true for the present invention since its basic concepts and understandings are fundamental in nature and can be broadly applied. The foregoing description of the specific embodiments so fully reveal the general nature of the invention that others can, by applying current knowledge, readily modify or adapt for various applications to suit specific applications. Such embodiments will not depart from the generic concept, and therefore should be deemed to fall within the meaning and range of equivalents of the disclosed and claimed embodiments. It should also be understood that the phraseology and terminology herein is for the purpose of description and not of limitation.

VI. CLAIMS

We claim:

1. A process for decomposing waste plastic comprising the steps of:
 - a. supplying waste plastic;
 - b. mixing said waste plastic with a diluent to create a solution;
 - c. controlling the content of said solution to assure that it will contain a sufficient free radical content when heated; then
 - d. heating said solution to a reactant temperature to substantially depolymerize the waste plastic; and
 - e. collecting the by products of said depolymerization process.
2. A process for the recycling of waste plastic comprising:
mixing said waste plastic, selected from comminuted waste plastic comprising polyethylene, polypropylene, polystyrene, polyethylene terephthalate, polyvinyl chloride, other waste plastic, and combinations thereof, with oil, selected from waste motor oil, fluidized catalytic cracker slurry oil, distillation tower vacuum bottoms, and heavy heating or bunker oil, and combinations thereof, and free radical catalyst precursor; heating to between 325 and 375°C for less than about one hour: and meeting process energy requirements by recycling back burnable products.
3. A process for decomposing waste plastic as described in claim 1 wherein said step of heating said solution to a reactant temperature to substantially depolymerize the waste plastic comprises the step of heating to less than about 400 °C.
4. A process for decomposing waste plastic as described in claim 1 wherein said step of heating said solution to a reactant temperature to substantially depolymerize the waste plastic comprises the step of heating to about 375 °C.
5. A process for decomposing waste plastic as described in claim 1

wherein said step of controlling the content of said solution to assure that it will contain a sufficient free radical content when heated comprises the step of adding an additional substance to said process.

- 5 6. A process for decomposing waste plastic as described in claim 1 wherein said step of controlling the content of said solution to assure that it will contain a sufficient free radical content when heated comprises the step of assuring an appropriate amount of free radical precursor is present in said process.
- 10 7. A process for decomposing waste plastic as described in claim 6 wherein said step of assuring an appropriate amount of free radical precursor is present in said process comprises the step of adding a particular waste plastic material to said process.
- 15 8. A process for decomposing waste plastic as described in claim 6 wherein said step of assuring an appropriate amount of free radical precursor is present in said process comprises the step of adding a substance chosen from a group consisting of polyvinyl chloride and polyurethane.
- 20 9. A process for decomposing waste plastic as described in claim 1 wherein said step of controlling the content of said solution to assure that it will contain a sufficient free radical content when heated comprises the step of sensing the relative amount of free radicals likely to be present in said solution after it is heated.
- 25 10. A process for decomposing waste plastic as described in claim 9 wherein said step of sensing the relative amount of free radicals likely to be present in said solution after it is heated comprises the step of ascertaining the reactant temperature of the solution.
- 30 11. A process for decomposing waste plastic as described in claim 1 and

further comprising the step of recycling a portion of said diluent.

12. A process for decomposing waste plastic as described in claim 1 and further comprising the step of recycling from 0 to 95% of said diluent.

13. A process for decomposing waste plastic as described in claim 11 wherein said step of recycling a proportion of said diluent comprises the step of recycling from 70% to 90% of said diluent.

14. A process for decomposing waste plastic as described in claim 1 wherein said step of mixing said waste plastic with a diluent to create a solution comprises the step of mixing said waste plastic with an oil.

15. A process for decomposing waste plastic as described in claim 1 wherein said step of mixing said waste plastic with a diluent to create a solution comprises the step of mixing said waste plastic with a heavy oil.

16. A process for decomposing waste plastic as described in claim 1 wherein said step of mixing said waste plastic with a diluent to create a solution comprises the step of mixing said waste plastic with a low value oil.

17. A system for decomposing waste plastic comprising:

- a. a first, second, and third supply means;
- b. a mix means responsive to at least two of said supply means;
- c. a reaction container connected to said mix means and responsive to said third supply means;
- d. a temperature control means connected to said reaction container;
- e. a collection means connected to said reaction container; and
- f. a control means wherein said third supply means is responsive to said control means.

18. A system for decomposing waste plastic as described in claim 17 wherein said first supply means supplies waste plastic and wherein said second supply means supplies a diluent.

5 19. A system for decomposing waste plastic as described in claim 18 wherein said second supply means supplies an oil.

10 20. A system for decomposing waste plastic as described in claim 19 wherein said second supply means supplies an oil selected from waste motor oil, fluidized catalytic cracker slurry oil, distillation tower vacuum bottoms, heavy heating or bunker oil, or combinations thereof.

15 21. A system for decomposing waste plastic as described in claim 17 wherein said temperature control means achieves temperatures of no more than 400 °C.

20 22. A system for decomposing waste plastic as described in claim 20 wherein said control means is responsive to the temperature within said reaction container.

VII. ABSTRACT

5 A process for recycling or decomposing waste plastic where such waste plastic is decomposed in a diluent such as hot oil through actions involving free radical precursor, such as polyvinyl chloride or polyurethane, is achieved at low temperature. The thermal decomposition (or pyrolysis) reaction is for about 1 hour at 375°C, and useable products, such as distillate, coke, and oil are recovered. Additionally the diluent may be recycled within the process.

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE
PCT BRANCH

In Re the Patent Application of:

Frank D. Guffey and Floyd A. Barbour

International Filing Number: _____

Priority Date: _____

For:

Process for Waste Plastic Recycling


Receiving Office:

RO/US

CERTIFICATE OF MAILING

I, Luke Santangelo, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521.
2. I have this day deposited the attached description, claims and abstract (21 pages) and with the United States Postal Service as "Express Mail" postage prepaid in an envelope addressed to: The Commissioner of Patents, and Trademarks, Box PCT, Washington, D.C. 20231, on March 2, 1994.



Luke Santangelo




Fig. 1




Fig 1

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE
PCT BRANCH

In Re the Patent Application of:

Frank D. Guffey and Floyd A. Barbour

International Filing Number: _____

Priority Date: _____

For:

Process for Waste Plastic Recycling


Receiving Office:

RO/US

CERTIFICATE OF MAILING

I, Luke Santangelo, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521.
2. I have this day deposited the attached one sheet of drawings with the United States Postal Service as "Express Mail" postage prepaid in an envelope addressed to: The Commissioner of Patents and Trademarks, Box PCT, Washington, D.C. 20231, on March 8, 1994.



Luke Santangelo

I hereby claim the benefit under 35, United States Code, §120 of any U.S. application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U.S. APPLICATIONS		STATUS (Check one)		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED
08/028,844	10 March 1993			X

PCT APPLICATIONS DESIGNATING THE U.S.

PCT APPLICATION NO	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)		
PCT/US94/002433	08 March 1994			

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

Send Correspondence to:

Direct Telephone Calls to:
(name and telephone number)

201	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
		Guffey	Frank	D.
		Laramie	Wyoming	U.S.A.
		5905 Chapparral Drive	Laramie	Wyoming 82070/U.S.A.
202	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
		Barbour	Floyd	Alan
		Laramie	Wyoming	U.S.A.
		4429 Comanche Drive	Laramie	Wyoming 82070/U.S.A.
203	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201

SIGNATURE OF INVENTOR 202

SIGNATURE OF INVENTOR 203

Frank D. Guffey

Floyd Alan Barbour

Attorney Docket: WRIPLASTIC
Express Mail: TB138968049US

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: (US original) 08/028,844 (new) _____
(PCT) PCT/US94/002433

Filed: (US original) March 10, 1993 (new) _____
(PCT) 08 March 1994

Group Art Unit: (US original) 1204 (new) _____

Examiner: (US original) D.C. Jones (new) _____

CERTIFICATE OF EXPRESS MAILING

I, Barbara A. Graves, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Form 1391 Combined Declaration for Patent Application and Power of Attorney with the United States Postal Service as "Express Mail" for mailing to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

DATED: September 6, 1995

Barbara A. Graves

Attorney Docket No: WRIPLASTIC

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Application of: Frank D. Guffey and Floyd Alan Barbour

For: Process for Plastic Recycling

Serial Number: _____

Filed: _____

Assignee: *The University of sm 8/21/95*
A Wyoming Research Corporation d/b/a Western Research Institute

POWER OF ATTORNEY

The University of sm 8/21/95
A Wyoming Research Corporation d/b/a Western Research Institute, hereby appoints Santangelo Law Offices, P.C., whose mailing address is 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521, including Luke Santangelo, whose registration number before the United States Patent and Trademark Office is 31,997, and William F. Vobach whose registration number before the United States Patent and Trademark Office is 39,411 as its attorney/agent to prosecute this application entitled "Process for Plastic Recycling" and to transact all business in the Patent Office connected therewith.

Date: 8/21/95


The University of sm 8/21/95
A Wyoming Research Corporation

by: Samuel M. Dorrence
Samuel M. Dorrence, Vice President and Assistant Secretary

UNITED STATES OF AMERICA)
)
STATE OF WYOMING)ss.
)
COUNTY OF Albany)

SUBSCRIBED AND SWORN to before me in the County of Albany, State of Wyoming, United States of America, by Samuel M. Dorrence, as Vice President, of University of Wyoming Research Corporation, this 21st day of August, 1995. *and Assistant smd 8/24/95 secretary*

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Wyoming.



Pat Hausel
Notary Public
My Commission Expires: October 2, 1995

635730-666666

Attorney Docket: WRIPLASTIC
Express Mail: TB138968049US

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: (US original) 08/028,844 (new) _____
(PCT) PCT/US94/002433

Filed: (US original) March 10, 1993 (new) _____
(PCT) 08 March 1994

Group Art Unit: (US original) 1204 (new) _____

Examiner: (US original) D.C. Jones (new) _____

CERTIFICATE OF EXPRESS MAILING

I, Barbara A. Graves, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Power of Attorney from the University of Wyoming Research Corporation with the United States Postal Service as "Express Mail" for mailing to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

DATED: September 6 1995

Barbara A. Graves

Express Mail No: TB138968049U

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9 (f) and 1.27 (b)) — INDEPENDENT INVENTOR

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9 (c) for purposes of paying reduced fees under section 41 (a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled Process for Waste Plastic Recycling described in

☒ the specification filed herewith

☐ application serial no. _____, filed _____

☐ patent no. _____, issued _____

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9 (c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9 (d) or a nonprofit organization under 37 CFR 1.9 (e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

☐ no such person, concern, or organization

☒ persons, concerns or organizations listed below*

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

FULL NAME The University of Wyoming Research Corporation
d/b/a Western Research Institute
 ADDRESS 365 North 9th Street, Laramie, Wyoming 82071-3395
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☒ NONPROFIT ORGANIZATION

FULL NAME _____
 ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME _____
 ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28 (b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Frank D. Guffey Floyd Alan Barbour
 NAME OF INVENTOR NAME OF INVENTOR NAME OF INVENTOR

Signature of Inventor

Signature of Inventor

Signature of Inventor

Date

Date

Date

Attorney Docket: WRIPLASTIC
Express Mail: TB138968049US

IN THE UNITED STATES PATENT AND
TRADEMARK OFFICE

In Re the Patent Application of:

Frank D. Guffey and Floyd Alan Barbour

For: Process for Waste Plastic Recycling

Serial Number: (US original) 08/028,844 (new) _____
(PCT) PCT/US94/002433

Filed: (US original) March 10, 1993 (new) _____
(PCT) 08 March 1994

Group Art Unit: (US original) 1204 (new) _____

Examiner: (US original) D.C. Jones (new) _____

CERTIFICATE OF EXPRESS MAILING

I, Barbara A. Graves, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 315 West Oak Street, Suite 701, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Verified Statement of Small Entity Status of Frank D. Guffey and Floyd Alan Barbour with the United States Postal Service as "Express Mail" for mailing to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

DATED: September 6, 1995

Barbara A. Graves

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9 (f) and 1.27 (d)) — NONPROFIT ORGANIZATION

I hereby declare that I am an official empowered to act on behalf of the nonprofit organization identified below:

NAME OF ORGANIZATION The University of Wyoming Research Corporation
ADDRESS OF ORGANIZATION d/b/a Western Research Institute
365 North 9th Street, P.O. Box 3395, Laramie, WY 82071-3395
University Station, Laramie, Wyoming 82071-3395

TYPE OF ORGANIZATION

- ☒ University or other institution of higher education
☐ Tax exempt under Internal Revenue Service Code (26 USC 501(a) and 501(c) (3))
☐ Nonprofit scientific or educational under statute of state of The United States of America
(Name of state _____)
(Citation of statute _____)
☐ Would qualify as tax exempt under Internal Revenue Service Code (26 USC 501(a) and 501(c) (3)) if located in
The United States of America
☐ Would qualify as nonprofit scientific or educational under statute of state of The United States of America if located
in The United States of America
(Name of state _____)
(Citation of statute _____)

I hereby declare that the nonprofit organization identified above qualifies as a nonprofit organization as defined in 37 CFR 1.9 (e) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code with regard to the invention entitled Process for Waste Plastic Recycling by inventor(s) _____ described in _____

- ☒ the specification filed herewith
☐ application serial no. _____, filed _____
☐ patent no. _____, issued _____

I hereby declare that rights under contract or law have been conveyed to and remain with the nonprofit organization with regard to the above identified invention.

If the rights held by the nonprofit organization are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9 (d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9 (d) or a nonprofit organization under 37 CFR 1.9 (e).

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME _____
ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

NAME _____
ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28 (b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING Samuel M. Dorrence
TITLE IN ORGANIZATION Vice President and Assistant Secretary smw 8/21/95
ADDRESS OF PERSON SIGNING 365 North 9th Street, P.O. Box 3395, Laramie, WY 82071-3395 smw 8/21/95
University Station, Laramie, Wyoming 82071-3395

SIGNATURE Samuel M. Dorrence DATE 8/21/95